

RETAIL WEIGHING SOLUTION™

SW-II series

Weighing & Counting Scale

As a simple weighing scale with a maximum of 1/30,000 resolution, SW-II is suitable in a variety of industrial environments, including traditional market, with its low body and ergonomics design.

Easy Grab Body



USB Port



USB



High Resolution for Weighing (Max. 1/30,000, Certificate 1/3,000 dual)

Easy Grab Body

USB Port for COMM. & Power

Rear Display for Customer

Scan with your smartphone
to find more products



CAS
www.globalcas.com

SW-II series

Weighing & Counting Scale



FEATURE

- High Resolution for Weighing (Max. 1/30,000, Certificate 1/3,000 dual)
- Easy Grab Body
 - Ergonomics design with a low body and comfortable handling



- USB Port for COMM. & Power (Option)



- Rear Display for Customer (Option)

- Rechargeable Battery (Option)

- A maximum of 1,000 hours when used with Mn or Pb battery together

OPTION

- RS-232 (Print, Command)
- Rear Display
- Rechargeable Battery & Adaptor
- USB Port
- SUS Tray

APPLICATION

- Open market, Farm, Industrial Environment

SPECIFICATIONS

MODEL	SW2-03	SW2-06	SW2-15	SW2-30
Capacity	3kg	6kg	15kg	30kg
e (Non-Certi.)	0.5g, 0.2g, 0.1g	1g, 0.5g, 0.2g	2g, 1g, 0.5g	5g, 2g, 1g
e (Certi.)	0.5/1(g) Dual	1/2(g) Dual	2/5(g) Dual	5/10(g) Dual
Resolution	1/3,000 ~ 1/30,000	1/3,000 ~ 1/30,000	1/3,000 ~ 1/30,000	1/3,000 ~ 1/30,000
Display	6Digit LCD (115x39.5mm) & Back light (White)			
Symbols	STABLE, ZERO, TARE, g, kg, lb, oz, PCS, Low Battery HI / OK / LO			
Keys	ZERO, TARE, MODE, FUNCTION KEY, UNIT, HOLD			
Functions	Hold, Unit Conversion, Counting-Counting SampleRange:10~100,200,300,400,500 Weight Comparison Function : hi, ok, low / Sleep Mode Function			
Operation Time	Approx. D size Battery = 500hr Or Pb Battery = 450hr (Backlight off) Approximately 1,000 hours consecutively when equipped with Mn Battery and Pb Battery altogether			
Option	RS-232 (Print, Command), Rear Display Rechargeable Battery And Adaptor, USB Port, SUS Tray			
Power	1.5V x 3 units (D size Battery) or Pb battery 4V 4Ah or 6V Adaptor			
Dimensions	245 (W) x 280 (D) x 110 (H)			
Platter Size	225 (W) x 190 (D)			
Product Weight	2.44 kg			

DIMENSION

